

CB MINERALS
 2 Madison Ave. #211
 Larchmont, NY 10538
 Tel: 914-777-3330 Fax: 914-777-3035
 WEBSITE: www.cbminerals.com
 E-Mail: info@cbminerals.com
 INDUSTRIAL MINERALS SINCE 1897

HIGH PURITY QUARTZ NC2-A 100-300

This material has impurities totally 10 ppm. used in quartz lamps, tubing, and crucibles

Chemical content of the solid material:

$\text{SiO}_2 > 99.999\%$

Content of other elements in ppm:

Element	NC A	
	Mean	Max.
Al	7,0	9,5
Ca	0,3	0,5
Fe	0,1	0,3
Na	0,8	1,2
K	0,3	0,6
Li	0,7	1,0
B	0,1	0,3
Co	□ 0, 01	
Cr	□ 0, 01	
Cu	□ 0, 01	
Mg	□ 0,05	
Mn	□ 0,01	
Ni	□ 0, 01	
Ti	□ 6	
Zr	□ 0,1	

Grain size distribution:

	Typical value	Limit
D_{10}	80 μm	Minimum 70 μm
D_{50}	155 μm	Range 135-200 μm
D_{90}	270 μm	Maximum 350 μm

The material is **calcined** at 1050°C according to our standard procedures.