

CHARLES B. CHRYSTAL CO., INC

689 Mamaroneck Ave.

Mamaroneck, NY 10543

Tel: 914 777 3330 Fax: 914 777 3035

WEB SITE: www.cbcrystal.com

E-Mail: info@cbcrystal.com

INDUSTRIAL MINERALS SINCE 1897

LIGHT GREY SLATE FLOUR

An insoluble, decomposed Silica, brownish or grayish in color. It is usually used as a soft, mild abrasive, in various types of polishes, for rubbing varnished woodwork and hard rubber and as an ingredient in the manufacturing of brake linings.

ANALYSIS

Silica	62.28%
Alkalies: K ₂ O Na ₂ O	4.9%
Alumina	20.71%
Ferric Oxide	7.65%
Lime & Magnesia: CaO + MgO	4.54%
Oil Absorption	22
Mesh	Min. 99% thru 325 Mesh
Specific Gravity	2.7
Bulking Value: Gallons per lb	0.443
Bulking Value: Pounds per gallon	22.58
PH as paste	8.1
Moisture	1.0% maximum at time of shipment

PACKING 50 lb multi-wall paper bags, wooden pallets.

CLASSIFIED Alumina Silicate CAS# 1335.30.4

ORIGIN USA

